

# Material Safety Data Sheet

Page 1 of 3 Issue date: 2010-10-18

Classified as Hazardous according to criteria of Worksafe Australia

## WOOLUBE OZSPRAY INDUSTRY

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### Technical, Sales and Emergency

##### AUSTRALIA

WOOLUBE LABORATORIES P/L  
ABN: 79088757582  
1 Turner Road  
Berowra Heights  
NSW 2082  
Ph: +61-2-94566300  
Fax: + 61-2-94566272  
E-mail: ghunt@woolube.com.au

##### EUROPE

+353 – (0)21 4354204

<b>Product Name:</b>	<b>WOOLUBE OZSPRAY INDUSTRY</b>
<b>Synonyms:</b>	LANOLIN SPRAY
<b>Suppliers Product Code(s):</b>	OZ750ML, OZ1L, OZ5L, OZ20L, OZ200L
<b>Use:</b>	WATER RESISTANT, WATER DISPERSENT, ANTI CORROSIVE, SPRAY FOR USE ON ALL FERROUS AND NON FERROUS MATERIALS SUCH AS STEEL, IRON, STAINLESS STEEL, COPPER, TIMBER, LEATHER, VINYL, CANVAS, PLASTICS ETC.
<b>UN Number:</b>	None allocated
<b>Proper Shipping Name:</b>	None allocated
<b>Dangerous Goods Class:</b>	None allocated
<b>Subsidiary risk:</b>	None allocated
<b>Packing Group:</b>	None allocated
<b>Hazchem Code:</b>	None allocated
<b>Poison Schedule:</b>	S5

### 2. HAZARD IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA**

**HAZARD CATEGORY:** None allocated

**ACUTE HEALTH EFFECTS:**

**Swallowed:** Slightly irritating, may cause lung damage.

**Eye:** May cause slight discomfort to the eyes but will not injure eye tissue.

**Skin:** Maybe mildly irritating to the skin due to solvent content.

**Inhaled:** Mists from the product may produce discomfort in the upper respiratory tract Inhalation hazard is increased at elevated temperatures.

**Chronic:** Very isolated cases of skin sensitisation to lanolin have been reported, however this incidence of allergy is extremely low, (NIOSH/TIC) thought to be 'swint' or sheep's' sweat/dandruff, inevitably extracted with the crude lanolin during processing.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE NAME	Proportion	CAS Number
LANOLIN ANHYDROUS	30%	8006-54-0
PROPRIETARY BLEND HYDROCARBON SOLVENTS	70%	64742-81-0

### 4. FIRST AID MEASURES

**Swallowed:** If swallowed, DO NOT induce vomiting. Give water or milk to rinse out mouth then give liquid slowly and as much as can comfortably be drunk. Seek medical advice.

**Eye:** If material is splashed into eyes, immediately, flush with plenty of water for 15 minutes, ensuring eyelids are held open. If irritation persists transport to hospital or doctor.

**Skin:** If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with soap and water. If irritation persists transport to hospital or doctor.

**Inhaled:** Move victim to fresh air. Lay patient down. Keep warm and rested

**First Aid Facilities:** Eye wash fountain, safety shower and normal washroom facilities.

**Advice to Doctor:** Treat symptomatically.

In case of poisoning contact;

# Material Safety Data Sheet

Page 2 of 3

Issue date: 2010-10-18

Classified as Hazardous according to criteria of Worksafe Australia

## WOOLUBE OZSPRAY INDUSTRY

In Ireland call the National Poisons Information Centre emergency telephone: 01 8379964.

In the UK call the National Poison Control Service emergency telephone: 0844 8920111.

### 5. FIRE-FIGHTING MEASURES

#### Fire/Explosion Hazard

If safe to do so, move undamaged containers from fire area.

**Hazardous Decomposition Products:** May decompose on heating emitting oxides of carbon. May emit acrid smoke.

**Fire Fighting Procedures:** Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined spaces, in oxygen deficient atmospheres or if exposed to products of decomposition. Full protective clothing is also recommended.

**Extinguishing Media:** Use extinguishing media suitable for surrounding fire situation.

**Flammability:** This material is a combustible liquid at elevated temperatures.

Slight fire hazard when exposed to heat or flame

### 6. ACCIDENTAL RELEASE MEASURES

**Minor Spills:** Material may be slippery when spilt. Walk cautiously. Collect and seal in properly labelled containers for disposal.

**Major spills:** Wear impervious gloves and safety glasses. Prevent by Bunding or damming or by any other means, spillage from entering drains or watercourses. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect residues and seal in labelled drums for disposal. Wash spill area thoroughly with water and suitable detergent.

### 7. HANDLING AND STORAGE

Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Keep containers closed, when not using the product. Store in original packages as approved by manufacturer.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure Standards:

No exposure standards have been assigned by the National Occupational Health & Safety Commission (NOHSC) for this product or any of the components:

#### Engineering Controls:

Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate unless the material is heated, reacted or otherwise changed in some type of chemical reaction, then the use of a local exhaust ventilation system is recommended.

#### Personal Protection Equipment:

**GLOVES:** Not normally required, however, if handling large quantities or if the skin is likely to be exposed to this product over prolonged periods, then the use of PVC or natural rubber is recommended.

**EYES:** Chemical goggles or face shield to protect eyes.

**RESPIRATORY PROTECTION:** Avoid breathing of vapours/gases. Select and use respirators in accordance with AS/NZS 1715/1716. The use of a dust mask (disposable) or a half-face respirator with P1 filter is recommended. Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Yellowish, tenacious, semisolid fatty substance with a slight characteristic odour
<b>Boiling Point Melting Point:</b>	195oC
<b>Vapour Pressure:</b>	0.06kPa @ 38oC
<b>Specific Gravity:</b>	0.85 - 0.89
<b>Flash Point:</b>	78oC Complies with Flash Point Determination in accordance with AS 2106.2:1999 using the Pensky-Martens apparatus conducted by Department of Mineral Resources, Mine Safety Laboratory.
<b>Flammability Limits:</b>	0.6 – 7.0 L.E.L. – U.E.L.
<b>Solubility in Water:</b>	Immiscible

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable under normal conditions of use.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Emits smoke and fumes when heated to decomposition.

**HAZARDOUS POLYMERIZATION:** Will not occur.

# Material Safety Data Sheet

Page 3 of 3

Issue date: 2010-10-18

Classified as Hazardous according to criteria of Worksafe Australia

## WOOLUBE OZSPRAY INDUSTRY

**INCOMPATIBILITIES:** Oxidizing agents.

**CONDITIONS TO AVOID:** High temperatures and incompatibles.

### 11. TOXICOLOGICAL INFORMATION

None allocated.

### 12. ECOLOGICAL INFORMATION

100% Biodegradable

### 13. DISPOSAL CONSIDERATIONS

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Suitable for disposal by an approved waste disposal agent.

### 14. TRANSPORT INFORMATION

**UN Number:** None allocated  
**Proper Shipping Name:** Lanolin Spray  
**Dangerous Goods Class:** None allocated  
**Subsidiary risk:** None allocated  
**Packing Group:** None allocated  
**Hazchem Code:** None allocated

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) 6th Edition. Not classified as a Dangerous Good according to the UN, DOT (US), IACO (IATA) or IMO (IMDG).

### 15. REGULATORY INFORMATION

(Due to solvent content)

**RISK PHRASES:** R65 May cause lung damage if swallowed  
**SAFETY PHRASES:** S2 Keep out of the reach of children  
S16 Keep away from sources of ignition – no smoking.  
S23/24/25 Avoid contact with skin and eyes.  
S36 Wear suitable protective clothing.  
S45 In case of accident or if you feel unwell, contact a Doctor or Poisons Information Centre and show them this MSDS.  
**POISON CLASSIFICATION:** S5

### 16. OTHER INFORMATION

**Approval No. IOA 5050 Commonwealth of Australia, Export Control Act 1982**

**High voltage testing by Energex resulted in the following:**

Dry Leakage Test 70KV/300mm..... 9.3 mA  
Wet Leakage Test 70KV/300mm..... 9.3 mA

This MSDS is prepared in accordance with Annex 4: Guidance on the preparation of Safety Data Sheets (SDS) of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS).

#### **Disclaimer**

The information herein is to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions are beyond our control we do not accept liability for any damages resulting from the use of, or reliance on, this information in inappropriate contexts.